

OAK SINGLE PLANK GRANDE



Supplier	Barlinek S.A.	
Product number	BC8-DBE1-OX4-XXZ-J14180-I	
Catalog number	1WG000712	
EAN Code	5906737965100 (PL)	

MATERIAL/APPERANCE			
Product description:	Product consists of three layers: surface layer – oak, middle and bottom layer -		
	pine		
Top layer:	One row of strips, Vintage grade		
Finish surface Layer:	Natural oxidative oil		
The connection system boards:	Cross edge - Barlock 5Gc system, transverse lock insert - HDF		
(for each package includes instructions			
assembly)			

CHARACTERISTICS OF THE SURFACE LAYER			
Surface appearance	Yellow-brown oak wood with natural features characteristic for this kind. The floor is characterized by grain variability and differences in oak colour. It darkens under the influence of UV rays, four-sided bevelled top layer, structured by brushing		
Hardness oak applied to the top layer of the board. The method according EN 13489 – testing Brinell (EN 1534)	average hardness 37 MPa		

Dimensional characteristics and acceptable deviations (consistent with standard PN-EN 13489). Dimensional characteristics and dimensional tolerances, marked at the time of leaving the manufacturer's facility, given in accordance with the type of multi-layer flooring elements.



DIMENSIONS OF AN INDIVIDUAL ELEMENT			
Dimensions (mm)	Tolerances		
Thickness: 14	Gap (between elements) ≤ 0,2 mm		
Length: 1800	+/-0,1%		
Width: 180	+/- 0,2mm		

Thicknesses boards measured in according with EN 13647

THICKNESSES BOARDS EN 13647			
Surface layer:	2,5 mm		
Middle layer:	9,5 mm		
Bottom layer:	2,0 mm		

PACKAGE			
Number of boards on a pack:	7 pcs. x 1800mm		
	V		
	6 pcs. x 1800mm+ 1 pcs. x 1772mm		
Pack:	2,26m2/pack, 40 pack/pallet = 90,4m2		

CHARACTERISTICS/ INSTALLATION INSTRUCTIONS/ WARRANTY			
Humidity board:	7% +/- 2%		
Installation on underfloor heating	Product designed in the system of electric and water floor heating solution.		
system:			
Warranty:	20 years		

DESCRIPTION OF SURFACE LAYER*			
Free class			
Vintage class			
Acceptable, without limit			
Acceptable, cracks up to 45mmx100mm, unhealthy up to 85mm			
Acceptable up to 40 mm in diameter			
Acceptable			
Varied, rustic			
Varied			
Acceptable , without limit			
Acceptable, without limit			
Acceptable up to 8 mm wide, up to 600 mm length			
Unacceptable			

^{*} According to the EN 13489 standard, 3% of different grade than indicated is acceptable. The limits of characteristic features of the product concern the upper layer of the element. The knots' fillings, especially in case of brushed surfaces, can be characterized by gaps which a deliberate effect of this kind of decorative surface. Measurement of wood characteristics according to EN 1310 standard.

ATTENTION: The natural features of the wood make every product a unique and unrepeatable item. Individual photographs in the sample books do not fully reflect the appearance of the product.



CARE OF NATURALLY OILED FLOORS			
BARLINEK WASH CARE -	PROPERTIES: Concentrated floor cleaning agent with plant-based soaps and natural care		
Soap for everyday floor care	additives. Cleans deep without smudging. Refreshes the floor and protects it against dirt.		
	APPLICATION: For all oil or wax coated wooden and cork floors and other oiled or waxed		
	wooden indoor surfaces, e.g. furniture. Also suitable for laminated floors.		
	Yield approx. 150 m²/l		
BARLINEK WAX CARE PLUS	PROPERTIES: Liquid agent for cleaning and maintaining wood, based on natural components.		
Agent for first and periodic	Regular use protects the surface of the wood, regenerates and preserves it.		
care of wood floors	APPLICATION: For all oil or wax coated wooden and cork floors and other oiled or waxed		
	wooden indoor surfaces.		
	Yield approx. 100m² /1 L		
	IMPORTANT: IMEDIATELY AFTER THE FLOOR IS LAID, IT IS RECOMMENDED TO PROTECT IT		
	WITH BARLINEK WAX CARE PLUS.		
BARLINEK MAGIC CLEANER	PROPERTIES: For periodic maintenance of wooden floors oiled with natural oil		
Agent for intensive cleansing	APPLICATION: For intensive cleaning of all natural oiled, waxed or lacquered wood or cork		
of dirt	surfaces.		
	Yield approx. 100m² /1 L		
	IMPORTANT: AFTER THE SURFACE HAS DRIED OUT COMPLETELY, APPLY WAX CARE PLUS		
	FLOOR CARE AGENT.		

RECOMMENDED FREQUENCY OF FLOOR MAINTENANCE*

	Barlinek Wash Care maintenance soap	Barlinek Wax Care Plus care agent	Magic Cleaner cleaning agent
Intensity of use	Everyday cleaning	Periodic care **	Thorough cleaning
Floors in rooms which are not intensively used, e.g. living rooms, bedrooms	Every 5-7 days	Every 6-12 months	Visually inspect
Floors in areas which are used with average intensity, e.g. stairs, corridors, office spaces	Every 3-5 days	Every 3-6 months	Visually inspect
Floors in intensively used areas, e.g. restaurants, shops, schools	Every 1-3 days	1-2 times per month	Visually inspect

IMPORTANT:

The floor should be cared for using only agents intended for this purpose.

* Use of care agents for floors oiled with natural oils made by manufacturers other than Barlinek may result in staining, discolouration of dyed or colourless floors or major changes to their slipperiness and sheen. Barlinek bears no responsibility for the effects of using agents made by other manufacturers.

All recommendations regarding the regularity of cleaning and caring for floors are given for reference only and depend on actual intensity of use. For these reasons they may not form the basis for warranty claims. Sand trailed or water spilt on the floor have very undesirable effects on it and it is vital to remove them. Thorough cleaning with Barlinek Magic Cleaner only needs to be done rarely and may be delayed considerably by regular cleaning and keeping the floor in a good condition.

** Apply first treatment **immediately** after floor installation, before normal use. Afterwards according to the table.